

Technical data	DISTO™ D110	DISTO™ D2
Typ. measuring accuracy	± 1.5 mm	± 1.5 mm
Range	0.2 up to 60 m	0.05 up to 100 m
Measuring units	m, ft, in	m, ft, in
X-Range Power Technology	●	●
Display illumination	●	●
Free App	●	●
Data interface*	Bluetooth® Smart	
Battery life time**	up to 10,000 measurements up to 20 h of operation	
Batteries	type AAA, 2 × 1.5 V	
Protection class	IP 54 (dust and splash water protected)	
Dimensions	120 × 37 × 23 mm	116 × 44 × 26 mm
Weight with batteries	92 g	100 g

\*) System requirements and other details can be found at [www.disto.com](http://www.disto.com)

\*\*\*) Reduced in Bluetooth® Smart mode

Functions	DISTO™ D110	DISTO™ D2
Distance measurement	●	●
Addition / subtraction	○	●
Area measurements	●	●
Volume measurement	○	●
Memory	○	10 results
Automatic end piece	○	●

PROTECT is subject to Leica Geosystems International Limited Warranty and PROTECT General Terms & Conditions set out under [www.leica-geosystems.com/protect](http://www.leica-geosystems.com/protect).

\* Available through free online registration within 8 weeks from the purchase date.



Laser class 2  
in accordance with IEC 60825-1

Dealer stamp

- when it has to be **right**

**Leica**  
Geosystems

# Leica DISTO™ D2

## Many functions – long range

### Multifunctional end piece

Whether you are taking measurements from corners, grooves or edges, with the multifunctional end piece you can always accurately position the Leica DISTO™ D2. The position of the end piece is automatically detected and taken into account. This prevents expensive measuring errors.



### Versatile thanks to useful measuring functions

Functions such as addition and subtraction, area and volume calculations make every measurement task child's play. The instrument stores the last 10 measurement results.



Free app:

**Leica DISTO™ sketch**



Available on the  
**App Store**



GET IT ON  
**Google play**

